

STACKING TUB ROLL OFF CONTAINER



STANDARD FEATURES

CWB Certified Welding

Our CWB certified welders & welding procedures guarantee exceptional weld quality. Eliminate breakdowns and reduce the overall life-cycle maintenance costs.

Double Tapered Sides

Double tapered sides allow you to stack up to 4 bins together! Stacking bins provide efficient transport or storage solutions.

Formed Floor and Back Posts

Provide improved structural strength and reduce the overall weight.

SCS Drop Forged Hinges

Heavy duty drop forged cast steel door hinges with grease fitting ensures an easy open door.

PRODUCT HIGHLIGHTS

- 15 29 cubic yard sizes
- 16' 20' lengths
- · Can be stacked up to 3 high for shipping





SCS CONTAINERS HAVE AN INDUSTRY LEADING 3-YEAR PARTS AND LABOUR WARRANTY

SPECIFICATIONS

- Hook lift Main rails 6" x 2" x 1/4" steel tube
- Cable pull Main rails 5" x 2" x 3/16" steel tube
- Cross members 3" x 3" x .120" formed Hi-tensile channel on 18" centers
- Door frame 4" x 3" x .120" Hi-tensile channel
- · Walls, door and front sheet, 12 GA Hot rolled sheet
- Floor 3/16" steel plate
- Rear post formed 3/16" steel plate
- Front rail 4" x 3" x 1/8" steel tube
- Side rails 4" x 3" x 1/8" steel tube
- Landing gear (wheel mount) 6" x 3" x 3/16" Hi-tensile formed
- Hinges Heavy duty dropped forged with grease fitting.

- ANSI 245.30-2008 Compliant Latch
 Carnegie Latch or Turn Buckle Ratchet Latch
- Wheels
 5" standard pipe with 1-1/4" extra heavy pipe hubs and
 1-3/16" cold rolled shaft
 All wheels have full length hubs for axle support and mount to the landing gear cross member with 3/8" formed steel plate
- Welding
 Inner and outer floor seams, front and rear wall seams and inside top rail seams are continuous welds
 - Two coats of anticorrosive primer on all exterior surfaces

 Two coats of industrial enamel paint in any single colour

SCS bins are manufactured to the highest quality standards. This reduces maintenance costs & increases productivity.

AVAILABLE OPTIONS



Upgrade To 3/16" Steel

Increase the strength and durability of your bin with 3/16" wall, front & door sheet steel.




Bin Roof or Lid

Tailor the bin to your specific application! We offer a fixed roof or hydraulic lid with access hatches as well as an available sealed rear door.



Dual Purpose

SCS Roll Off Bins can be fit for any under structure hook lift, cable, live roll, bail hook (Dempster) or dual purpose system.



Heavy Duty Flooring

Increase the strength and durability of your Stud Wall with heavy duty floor options 1/4 , 5/16 and 3/8 thick steel plate.

TOLL FREE: 1 (877) 727-7833 | EMAIL: SALES@SCSINC.CA FOR MORE PRODUCT INFORMATION VISIT SCSINC.CA

