



MANUFACTURING INC

COMPACTOR RECEIVER ROLL OFF CONTAINER



STANDARD FEATURES

CWB Certified Welding

Our CWB certified welders & welding procedures guarantee exceptional weld quality. Eliminate breakdowns and reduce the overall life-cycle maintenance costs.

Manufactured Above Industry Standard

SCS manufacturers all stud wall roll off bins above industry standards! SCS bins have additional wall studs and cross member spacing, to create a stronger more durable container.

Multiple Latch Designs

SCS Stud Wall Roll Off Containers have 3 door latch designs to choose from. Each application is unique, get a latch to suit your jobs exact needs.

SCS Drop Forged Hinges

Heavy duty drop forged cast steel door hinges with grease fitting ensures an easy open door.

FEATURES

- 30, 40 & 44 cubic yards
- 18' - 22' lengths




SCS CONTAINERS HAVE AN INDUSTRY LEADING 3-YEAR PARTS AND LABOUR WARRANTY

SPECIFICATIONS

- Hook Lift Main rails 6" x 2" x 1/4" steel tube
- Cable Pull Main rails 6" x 2" x 3/16" steel tube
- Cross members 3" x 3" x .120" formed Hi-tensile channel on 18" centers
- Vertical studs 6" x 3" x .120" formed Hi-tensile channel on 48" centers
- Door frame 4" x 3" x 3/16" steel tube
- Walls, door and front sheet, 10 GA Hot rolled sheet
- Floor 3/16" steel plate
- Rear post - Formed 3/16" Hi tensile channel
- Landing gear (wheel mount) 6" x 3" x 3/16" Hi-tensile formed channel
- Hinges – 3/4" plasma cut plate with 1-3/16" cold rolled pin
- Carnegie style vertical latch
- 2-1/2" NPT fire suspension bungs
- Latch - SCS easy open design
- Wheels
 - Front and rear
 - 5" standard pipe with 1-1/4" extra heavy pipe hubs and 1-3/16" cold rolled shaft
 - All wheels have full length hubs for axle support and mount to the landing gear cross member with 3/8" formed steel plate
- Welding
 - Inner and outer floor seams, front and rear wall seams are continuous welds

SCS bins are manufactured above industry standard. Reduce your maintenance costs & maximize uptime.

AVAILABLE OPTIONS



10 Gauge Steel

Increase the strength and durability of your bin with 10 gauge steel or a 3/16" wall, front & door sheet.



Bin Roof or Lid

Tailor the bin to your specific application! We offer a fixed roof or hydraulic lid with access hatches as well as an available sealed rear door.



Dual Purpose

SCS Roll Off Bins can be fit for any under structure hook lift, cable, live roll, bail hook (Dempster) or dual purpose system.



Heavy Duty Flooring

Increase the strength and durability of your Stud Wall with heavy duty floor options 1/4", 5/16" and 3/8" thick steel plate.

TOLL FREE: 1 (877) 727-7833 | EMAIL: SALES@SCSINC.COM
FOR MORE PRODUCT INFORMATION VISIT SCSINC.COM



MANUFACTURING INC