



MANUFACTURING INC

FIXED TUB STYLE GRAVEL BODY



STANDARD FEATURES

Body Configuration

Hardox 500tuf floor, walls, front and tailgate.

Tub Style

Large radius formed walls provide excellent durability and material clearing.

Hoist

Bottom mounted telescoping cylinder for improved stability.

Air Tarp

Underbody cylinder air tarp with side arms.

Tailgate

Top-hinged with heavy-duty pivots; standard with 3' high lift gate.

FEATURES

- 12 - 15 cubic meters
- 16' - 20' lengths
- 1 Year Parts and Labour Warranty



SPECIFICATIONS

- 1/4" formed steel long sill
- 1/4" Hardox 500tuf floor sheet
- 3/16" Hardox 500tuf round bottom walls
- 3/16" Hardox 500tuf front and door skin
- Standard 36" hydraulic highlift gate with air actuate gate release and spreader chains
- Tailgate- formed double wall
- 1/4" reinforced formed rear posts with lights
- Air tarp
- Aluminum powder coated fenders
- Side boards, 2" x 10" fir
- Steel side board caps
- Shovel holders
- Welding
 - Inner and outer floor seams, front and rear wall seams and inside top rail seams are continuous welds
- Painting
 - Two coats of epoxy primer on all exterior surfaces
 - Two coats of poly urethane top coat in any single colour



SCS products are manufactured to the highest quality standards. This reduces maintenance costs & increases productivity.

OTHER FEATURES



Sideboards

Removable fir boards are provided to increase capacity, allowing for flexible adjustment based on load requirements.



Longsills

Fabricated full-length structural members, fully welded to the floor and front bulkhead.



CWB Certified Welding

Our CWB certification guarantees exceptional weld quality. This helps contribute to the overall life-cycle of our products.



Hardox Steel

The use of Hardox steel provides exceptional strength and durability while minimizing weight.

TOLL FREE: 1 (877) 727-7833 | EMAIL: SALES@SCSINC.CA | SCSINC.CA

